

## **Tehniskā specifikācija platformām PTL-R**

Modelis	PTL-10R	PTL-12R	PTL-15R	PTL-20R	PTL-20R	PTL-12RL	PTL-15RH
Tehniskā kravnesība, kg	12 000	14 000	16 000	24 000	24 000	12 000	15 000
Reģistrējamā kravnesība, kg	10 000	12 000	15 000	20 000	20 000	12 000	15 000
Transporta ātrums, km/h	40	40	40	40	40	25	25
Pašmasa, kg	3 500	4 400	4 800	5 200	5 500	4 250	4 800
Platformas gabaritmēri, mm							
Garums	6 250	7 500	9 250	11 250	11 250	5 200 + 3 400	5 200 + 5 000
Platums	2 500	2 500	2 500	2 500	2 500	2 500	3 000
Augstums	1 100	1 100	1 100	1 100	1 100	800	0-1100
Pamatnes biezums, mm	4	4	4	4	4	4	4
Šasijas ass izmērs, mm	90x90 mm	90x90 mm	120x120 mm	120 x 120 mm	120 x 120 mm	120 x 120 mm	150 x 150 mm
Asu skaits, gab.	2	2	2	2	3	1	1
Stūrējošā ass, gb	-	-	-	0	1	-	-
Grozāma sakabes cilpa					Standarts		
LED lampas					Standarts		
Atbalsta kāja	Mehāniska				Hidrauliska		
Piekabes šasija	Atsperu	Atsperu	Atsperu	Atsperu	Atsperu	Bez atspojuma	Bez atspojuma
Riepas	550/45-22.5	550/45-22.5	560/45R22.5	560/45R22.5	560/45R22.5	23.1R26	30.5R32
Bremzes	pneimatika	pneimatika	pneimatika	pneimatika	pneimatika	pneimatika	pneimatika
Min traktora jauda	100	120	140	170	170	130	180
Standarta krāsa					Kravas kaste JD zaļa vai sarkana, rāmis pelēks		
Garantijas laiks					2 gadi		
<b>Papildaprīkojums</b>							
Hidrauliska atbalsta kāja	+	-	-	-	-	-	-
Dīseles amortizācija	+	+	+	+	+	+	+
Nestandarta krāsa	+	+	+	+	+	+	+
K80 sakabe	-	-	+	+	+	-	-
Sturējamā ass	-	-	+	+	+	+	+
Sakabe + izvadi otrai piekabei	+	+	+	+	+	-	-
Trīs pozīciju gala borti	+	+	+	+	+	+	+
Hidrauliskie sānu borti	+	+	+	+	+	+	+
Kāpnes	+	+	+	+	+	+	+
Kaste siksniņam	+	+	+	+	+	+	+
LED lampas sānos	+	+	+	+	+	+	+
Kombinētās bremzes	+	+	+	+	+	+	+
Hidrauliskās bremzes	+	+	+	+	+	+	+
Riepas 600/40-22.5	-	+	+	+	+	-	-
Riepas 710/45R22.5	-	-	-	+	+	-	-